

14404

Closet Carrier Single, Left Hand Offset And 2" Vent Specification

Josam 14404 series coated cast iron single vertical 4" no-hub left-hand offset fitting with 2" no-hub vent, adjustable carrier body, invertible for siphon jet or blowout closets, with ABS extension with integral test cap, pylon feet, plated hardware and neoprene fixture gasket.

- □ Recommend feet be secured to floor with 1/2" bolts and anchors (by others).
- Solution For siphon jet roughing over 6" or blowout roughing over 12-1/2" specify on order.
 - Siphon jet dims shown. For blowout dims, use:
- ∠ Min 11" and max 16 1/2".





-SD	Special duty 500 LB carrier
-VP	Vandal-proof trim
-1	Positioning frame
-6	Supply pipe support (specify type of pipe)
-21	Hanger type closet adapter
-SDH	Special duty high 750 LB carrier

-30	Cast iron adj. ext. w/ connector
-30-2	Cast iron adj. ext. w/ connector and test cap
-50	No-hub high auxiliary inlet, opposite vent
-54	Threaded high auxiliary inlet, opposite vent
-XSD	Extra special duty 1,000 LB carrier

Josam product specifications in U.S. customary units are approximate and provided for reference only. For precise measurements, please contact Josam Technical Support. Josam reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Josam products previously or subsequently sold.

Notes:

(JOSAM)

T: (800) 365-6726 • Josam.com A WATTS Brand

ES-J-14404 2505 © 2025 Josam